

```

linux-3.3.7/drivers/net/wireless/ath/
hw.c → ath
regd.c → ath
main.c → ath
key.c → ath
debug.c → ath
ath5k/
caps.c → ath5k
initvals.c → ath5k
eeprom.c → ath5k
gpio.c → ath5k
desc.c → ath5k
dma.c → ath5k
qcu.c → ath5k
pcu.c → ath5k
phy.c → ath5k
reset.c → ath5k
attach.c → ath5k
base.c → ath5k
led.c → ath5k
rfkill.c → ath5k
ani.c → ath5k
sysfs.c → ath5k
mac80211-ops.c → ath5k
debug.c → ath5k
ahb.c → ath5k
pci.c → ath5k
ath9k/
beacon.c → ath9k
gpio.c → ath9k
init.c → ath9k
main.c → ath9k
mci.c → ath9k
recv.c → ath9k
xmit.c → ath9k
ahb.c → ath9k
pci.c → ath9k
rc.c → ath9k
debug.c → ath9k
dfs.c → ath9k
dfs_debug.c → ath9k
ani.c → ath9k_hw
ar5008_phy.c → ath9k_hw
ar9002_calib.c → ath9k_hw
ar9002_hw.c → ath9k_hw
ar9002_phy.c → ath9k_hw
ar9003_calib.c → ath9k_hw
ar9003_hw.c → ath9k_hw
ar9003_phy.c → ath9k_hw
ar9003_rtt.c → ath9k_hw
calib.c → ath9k_hw
eeprom_4k.c → ath9k_hw
eeprom_9287.c → ath9k_hw
eeprom.c → ath9k_hw

```

\$(CONFIG\_ATH\_DEBUG)  
\$(CONFIG\_ATH5K)  
\$(CONFIG\_ATH5K\_DEBUG)  
\$(CONFIG\_ATH5K\_AHB)  
\$(CONFIG\_ATH5K\_PCI)  
\$(CONFIG\_ATH9K)  
\$(CONFIG\_ATH9K\_AHB)  
\$(CONFIG\_ATH9K\_PCI)  
\$(CONFIG\_ATH9K\_RATE\_CONTROL)  
\$(CONFIG\_ATH9K\_DEBUGFS)  
\$(CONFIG\_ATH9K\_DFS\_CERTIFIED)  
\$(CONFIG\_ATH9K\_DFS\_DEBUGFS)

```

eeprom_def.c → ath9k_hw
hw.c → ath9k_hw
ar9002_mac.c → ath9k_hw
ar9003_eeprom.c → ath9k_hw
ar9003_mac.c → ath9k_hw
ar9003_mci.c → ath9k_hw
ar9003_paprd.c → ath9k_hw
mac.c → ath9k_hw
btcoex.c → ath9k_hw
common.c → ath9k_common
hif_usb.c → ath9k_htc
htc_drv_beacon.c → ath9k_htc
htc_drv_gpio.c → ath9k_htc
htc_drv_init.c → ath9k_htc
htc_drv_main.c → ath9k_htc
htc_drv_txrx.c → ath9k_htc
htc_hst.c → ath9k_htc
wmi.c → ath9k_htc
htc_drv_debug.c → ath9k_htc
carl9170/
...
ath6kl/
...

```

\$(CONFIG\_ATH9K\_HTC\_DEBUGFS)  
\$(CONFIG\_CARL9170)  
\$(CONFIG\_ATH6KL)